

Silicone Rubber Insulated Heating Elements

- Custom Design
- Etch Foil and Wire Wound Technology
- Precise Even Heating
- Flexible and Lightweight
- Moisture and Chemical Resistant
- Wide Temperature Range -60 to 230°C
- UL and VDE Approval available
- Low Smoke and Low Toxicity options available
- Full Design and Manufacturing Service

Physical Characteristics:

- Weather & Ageing resistance – Very Good
- Ozone resistance – Very good
- Gas Permeability – Adequate
- Steam Resistance – Good:
up to 130°C or 2.5 bar
- Fungus & Bacteria Resistance- Very Good
- Combustibility-Variou Flame retarding materials available
- Good Resistance to – Acetone, Alcohol, Formic Acid, Brake Fluid, Chlorodiphenyl, Acetic Acid, Greases, Polar Solvents, Hydrochloric Acid 10%, Sulphuric Acid 10%, Waxes, Plasticisers
- Thermal Conductivity-Watt/Meter/K 0.22
- Specific Heat- Joule/Kg/K 1623

Holroyd Components Ltd.
Shire Hill Industrial Estate,
Saffron Walden, Essex
CB11 3AQ United Kingdom
Tel: +44 (0) 1799 523177
Fax: +44 (0) 1799 513714
sales@holroydcomponents.com
www.holroydcomponents.com



ISO 9001:2008
FM 558985



UL and VDE approved manufacturing facilities

Applications:

Silicone rubber is ideally suited for the production of heater mats with it's low thermal mass and superb electrical insulation properties, it allows high power densities with fast response to temperature control. With silicones wide temperature range tolerance of -60°C to 230°C, being thin and lightweight it has a distinct advantage over other forms of heating elements. Where direct precise and intimate heating is required silicone heaters are the ideal solution.

Wire Wound:

Using evenly spaced resistance wires laminated between sheets of silicone, wire wound mats are ideal for prototyping or problem solving applications. Manufactured to customer specifications they can be made in a limitless range of shapes and sizes. High flexibility can be obtained using tough, robust materials which are finding ever increasing applications in industries.

Etch Foil:

Computer designed chemically etched foil tracks are laminated between thin sheets of silicone to give precise even heating. Suitable for both low and high volume production Etched foil heaters have rapid heat up properties with precise temperature control. Available in a limitless range to customer specification etch foil heaters provide heating solutions in a multiple of industries.

| | | |
|---------------|--|--|
| Type: | H/SR=Holroyd Silicone Rubber | |
| | H/SR-A=Holroyd Silicone Rubber Adhesive | |
| Dimensions: | Width 940mm maximum | |
| | Length 3000mm maximum | |
| | Nominal Thickness H/SR | 0.7mm-3.0mm |
| | H/SR-A | 0.8mm-3.0mm |
| Construction: | Two ply woven glass textile reinforced silicone rubber | |
| Temperature: | H/SR | -60°C to +200°C maximum continuous 230°C short term |
| | H/SR-A | -20°C to +180°C maximum continuous 230°C short term |

Installation & Fixing:

Our self adhesive option is a quick and simple fixing method which provides superb bonding results to many surfaces including low energy materials. Where removal of the heater is necessary alternative fixings are available such as hooks and straps as well as Velcro and magnetic backed options. Most mechanical fixing methods can be accommodated.

www.holroydcomponents.com